

## **ADVANTAGES**

- Professional Inverter equipment for continuous wire, coated electrode and TIG welding.
- Simple to use with easy menus to configure in manual / classic mode.
- Adjustable Arc Force to weld cellulosic electrode and improve TIG response.
- Easy polarity reversal to use hollow wire.
- Real-time current and voltage indicators.
- Superior inverter technology, with light and very powerful transformer, only 45 Kg for 350 A at 60%.
- Manufactured under strict European specifications 2011/65 / EU, 2014/35 / EU, 2014/30 / EU and IEC 60974.
- Suitable for 3x400 generators. Able to withstand voltage deviations between ± 10%.
- Professional wire winder, with 85W motor and two push pull rollers, safe and stable wire reducer, suitable for all kinds of coils.
- Great mobility between winder and machine, thanks to the 10m of compact connection hose, with a unique cover for all connections.
- Intelligent control of voltage, current and speed from the winder unit



SHEET Current (Amps) (A, X=60%) 350 A Thread Electrode Weight Voltage Generator Size 114 x 30 x 90 cm





0.8 - 1.2 mm

3 x 400 V

8 mm

25 KVA

**45** kg

## **INCLUDES**

_			
- Power	cable	/ Pure	conner

- Earth cable with clamp / Pure copper

- Clamp Electrode Cable / Pure Copper

- Winding hose - compact equipment

- Gas connection pipe

- High capacity external winder with:

2 Rollers 1.2 mounted

2 Rollers 0.8 - 1.0 extra.

- BINZEL 36AK / 4m torch

- Support for gas cylinder with protective flanks.

- Rollers for 2x0.8 - 1.0 / 2x1.0 - 1.2

- 6 replacement contact tips 2x0.8 - 2x1.0 - 2x1.2

- 1 Flowmeter

- 4 Fuses 3.5 A 250V.

- 1 Tips Kev.

- 1 Clamp.



3m x 4mm2

3m x 40mm<sup>2</sup>

3m x 40mm<sup>2</sup>

10m

12m