



WBP 10

Angle drill up to 10 mm

Extremely small angle drill for working in difficult-to-reach spots.

Product number: 7 205 51 60 00 0

Details

- > FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- > Particularly flat and slim design with 17 mm width across corners and 96 mm gearbox head height for work in tight spaces and corners.
- > Flexible and universal use thanks to clockwise and reverse running for thread cuts up to M6.
Metal gear head.
- > Tapered drill shaft.
- > High-precision metal drill chuck.
- > High concentricity.
- > Distortion-free barrel-type motor housing.
- > FEIN Sensitive Handle.
- > 5 metre cable.

Price includes

- ✓ 1 3-jaw chuck up to Ø 10 mm
- ✓ 1 drill chuck key



Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Input	500 W	Sound pressure level LpA Uncertainty of measured value KpA	82 dB 3 dB
Output	270 W		
Speed, full load	0 - 1,030 rpm	Sound power level LWA Uncertainty of measured value KWA	93 dB 3 dB
Speed, no load	0 - 1,830 rpm		
Torque at max. output power	8 Nm	Sound peak value LpCpeak Uncertainty of measured value KpCpeak	96 dB 3 dB
Stall torque	21 Nm		
Drill chuck clamping width	0.8 - 10 mm	Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	3 m/s ² 1,5 m/s ²
Capacity in steel \varnothing	10 mm		
capacity in \varnothing stainless steel	10 mm		
Capacity in alu \varnothing	15 mm		
Capacity in wood \varnothing	25 mm		
Tapping	M 6		
Cone at drill shaft	B 10		
Width across corners	17 mm		
Gearbox head height	96		
Cable with plug	5 m		
Weight according to EPTA	1.50 kg		



FEIN

Application examples

